

Nokia 7750 Service Router

Release 23

The Nokia 7750 SR series of IP routers delivers high performance with the speed, capacity, power efficiency, flexible capability, network security and automation tools essential for IP networking in the 5G and cloud era. With continuous design innovation and proven investment protection, the 7750 SR helps build an IP network that can evolve with changing needs for years to come.

Overview

As networks experience unprecedented traffic growth and unpredictable demands, operators are on a quest to meet ever-increasing performance requirements while rolling out new services quickly over a secure, self-defending network.

The 7750 SR addresses these imperatives, enabling operators to build a bigger, secure, automated and sustainable network with a superior return on investment.

With four variants, the 7750 SR scales capacity from 1.5 Tb/s full duplex (FD) up to 13.5 Tb/s FD and delivers performance certainty for demanding network roles. Universal QSFP-DD, QSFP28 and SFP28 connectors enable high-density 400GE, 100GE, 25GE and 10GE networking environments.

At the heart of the 7750 SR is Nokia 3.0 Tb/s FP4 silicon. A fully programmable network processor, it is fully deterministic and power efficient, enabling diverse deployment needs, and is essential for high performance routing. Powered by the comprehensive features of the Nokia Service Router Operating System (SR OS), the 7750 SR supports a full array of network functions and services. These industry-leading capabilities enable network designs without trade-offs among performance, capacity, scale and power consumption.



7750 SR-12e



7750 SR-12



7750 SR-1



7750 SR-7



To protect against increasing security threats, the 7750 SR takes a silicon-embedded approach to IP network security. Acting as a highly precise attack sensor and mitigation element, the 7750 SR makes the network part of the solution to help neutralize DDoS attacks — all without impacting router performance.

The Nokia 7750 SR product family consists of the Nokia 7750 SR series, the Nokia 7750 SR-s series, the Nokia 7750 SR-a series and the Nokia 7750 SR-e series.

Features and benefits

Speed and capacity

Highly scalable platform

Available in four system variants, the 7750 SR is highly scalable to fit in a variety of network locations and deployment models in high-density 10GE, 100GE and 400GE networking environments.

The compact 7750 SR-1 is a modular, single-slot system supporting up to 1.5 Tb/s FD and up to 4.0 Tb/s FD with intelligent aggregation. It supports QSFP56-DD, QSFP28-DD, QSFP28, QSFP+, SFP28 and CFP2-DCO connectors along with flexible breakout options, including 10 x 10GE, 2 x 100GE and 4 x 100GE.

The chassis-based 7750 SR-7 and SR-12 are equipped with five and 10 slots respectively, offering 800 Gb/s FD per slot and up to 1.2 Tb/s FD with intelligent aggregation. It supports QSFP56-DD, QSFP28-DD, QSFP28, QSFP+, SFP28 and CFP2-DCO connectors. The chassis-based 7750 SR-12e is equipped with nine slots and supports up to 1.5 Tb/s FD per slot and up to 4.0 Tb/s FD with intelligent aggregation. It supports QSFP56-DD, QSFP28-DD, QSFP28, QSFP+, SFP28 and CFP2-DCO connectors. These systems also support flexible breakout options, including 10 x 10GE, 4 x 25GE, 2 x 100GE and 4 x 100GE.

The modular system architecture and universal line card connectors give the 7750 SR flexible interface expansion options and economic scaling of switching capacity, density and connector type.

For port extension options, Nokia 7210 Service Access Switch (SAS) satellites offer local or remote GE, 10GE and SONET/SDH port expansion through an external system.

400GE IP-optical integration

The 7750 SR is ready for the 400GE era. 400G ZR and 400G ZR+ pluggable transceivers are supported in QSFP56-DD form factors to optimize density and performance for high-capacity data center interconnect, metro and regional access, edge and core network applications.

The 7750 SR line card has an energy-efficient design and ample cooling to support 400G ZR and 400G ZR+ optics. The innovative mechanical design of the 7750 SR line cards enables operators to maximize density and usability of coherent optics. This Nokia design advantage enables operators to equip up to 72 x 400G ZR and 400G ZR+ transceivers in a deployed 7750 SR-12e without changing hardware.

A standards-based generalized MPLS (GMPLS) user-network interface (UNI) enables IP-optical control plane integration, allowing the 7750 SR to efficiently coordinate IP routing and transport requirements across administrative boundaries and to dynamically set up optical segments and end-to-end transport connections.

Power efficiency for sustainability

Power-efficient design innovations on the 7750 SR increase the sustainability of IP networks through reduced emissions.

The FP4 chipset architecture enables line card designs with fewer FP4 complexes and fewer components on each board to lower power consumption. The FP4 memory architecture is also exceptionally power efficient. Power consumption scales with licensing level to drastically reduce power when only a fraction of a line card is in use. With Nokia FP4, these and other mechanisms are dynamic, enabling each 7750 SR system to automatically adapt to lower power consumption.



FP4 silicon reduces power consumption by 50 percent over the previous generation Nokia FP3 silicon while offering up to six times more capacity. With the 7750 SR, this power reduction is realized with full capacity and features enabled and deterministic performance under all network operating conditions. Multiple license configurations, including intelligent aggregation and a choice of line card assembly options, give operators the flexibility to design network locations for power consumption along with performance, capacity and scale to achieve sustainability goals.

Flexible capability

Network processor-based architecture

Every generation of FP silicon has been based on a network processor (NP) design. An NP offers the highest degree of flexibility and programmability in the industry. With a fully programmable data path, the data path is fully upgradable to new hardware-based performance standards with a simple software update. Fixed-function silicon with pre-defined upgradability pales in comparison.

Modern networks today rely on segment routing, EVPN, 1588 edge timestamping and countless other standards that were not conceived 10 years ago. FP's NP-based architecture has been able to turn on these capabilities with hardware-based performance, eliminating the need for hardware-based upgrades. This is a true measure of programmability and investment protection. With uncertainty around future evolving network standards, an NP-based architecture delivers the lowest TCO compared to any other chipset architecture on the market.

Deterministic performance: Tables, buffers and QoS

FP4 is fully deterministic across tables and buffers under all network loading conditions. This enables performance certainty at full scale and under real-world network conditions. This capability is powered with line-rate packet processor intelligent memories coupled with fast buffer memories. Where other industry packet processors rely on non-line rate memories for buffering, for tables, or potentially for both, FP4 avoids their performance sacrifice

to deliver 10 years of predictable performance. A line rate memory system will always outperform a non-line rate memory system under all network loading conditions without exception.

FP4 is fully buffered with both deep line rate ingress and deep line rate egress buffers. It supports full packet pre-classification and pre-buffering in front of the packet processor equally, ensuring a superior level of performance for all critical flows and guarantees the traffic that matters most, regardless of port configuration. It supports a full set of QoS with up to eight queues per service, hardware-assisted H-QoS, and an industry leading total number of queues and policers to support all necessary QoS features from simple to complex in a highly granular way. QoS capabilities support tremendous capability for BNG and quad-play services but can equally be scaled to deliver optimized lean performance.

Pay-as-you-grow licensing

A flexible pay-as-you-grow licensing model for the FP4-based line card provides a choice of entry points for immediate requirements and the ability to scale in place for evolving needs with software-only upgrades. This provides cost savings, ensuring operators pay for only the required functionality.

Capacity licenses provide bandwidth, connector density and intelligent aggregation mode options. Functional licenses scale services through control options on egress hardware queues and egress policers. Each FP4 line card supports multiple combinations of these licenses to cost-effectively scale capacity and functionality attributes while protecting hardware investments.

Intelligent aggregation

Intelligent aggregation is a capability that allows the 7750 SR to cost-effectively aggregate port capacity beyond the forwarding capacity of a delivered line card. The 7750 SR enables up to 4 Tb/s FD of intelligent aggregation per system and line card, and it does this in a deterministic way with full respect for QoS and packet priority.

Intelligent aggregation allows for guaranteed QoS with full pre-buffering and pre-classification in front of our packet processor when used in an aggregation

configuration. This enables the 7750 SR to collapse full layers of pre-aggregation in front of systems or, if ports are constrained on an edge or core node, to expand the number of available ports without adding more line cards and to continue to perform in a fully deterministic way under all network loading conditions. As a result, intelligent aggregation can be a significant driver of sustainability and both CAPEX and OPEX savings.

Proven investment protection

Proven across four generations of FP silicon, each new generation of FP silicon supports seamless backwards compatibility to extend the product life of deployed systems. Line card designs anticipate future requirements for higher powered optics and speeds along with flexible licensing to cost-effectively scale capacity.

FP3-based 7750 SR-7, SR-12 and SR-12e systems can seamlessly be upgraded to FP4 to enable higher capacity, connector speed and other capabilities without service impact and without requiring additional control, power or fan upgrades. With an FP4-based switch fabric and the latest control processor module, these systems support both FP3- and FP4-based line cards with full backwards compatibility. This means both variants interwork in the same chassis at the same time with full capacity, scale and features and no interworking caveats for best in-class investment protection.

FP4 has a fully programmable data path and is upgradable to new hardware-based performance standards with a simple software update. The programmability of FP silicon and Nokia SR OS integration ensures quick adaptation of new standards and features without the need for hardware-based upgrades. This means that adding new silicon enhancements, capacity and capabilities is field extensible, without a forklift.

Combined, these attributes provide the best investment protection in the industry and allow operators to build an IP network that can evolve with changing needs for years to come.

Comprehensive features

Nokia's feature-rich 64-bit SR OS addresses the full spectrum of IP routing requirements. With

comprehensive QoS, IP/MPLS, segment routing and model-driven management features, the 7750 SR has the intelligent capabilities and tools to define and deliver the most stringent SLAs and end-user quality of experience (QoE) requirements.

The 7750 SR supports tens of thousands of IP flows and access control lists (ACLs) with high performance at scale even when multiple advanced features are enabled concurrently. It supports advanced push-based telemetry models to stream flow-level data and insights in near-real time for network automation and DDoS security.

Leveraging the Nokia SR OS, the 7750 SR supports value-added services and network functions through the 7750 SR Extended Services Appliance (ESA) or integrated services adapters (ISAs), including application assurance (AA), Layer 7 stateful firewall, network address translation (NAT) and gateways.

Platform versatility

Demanding network roles demand in-house silicon. The 7750 SR supports a full array of network functions and services. Leading SR OS capabilities combined with licensing and line card modularity provides complete configuration versatility to support multiple, demanding network roles with deterministic performance on a single platform.

For service providers, the 7750 SR is deployed in mission-critical WAN, data center and aggregation networks to support IP edge, gateway and core functions for advanced residential, mobile and enterprise services, including:

- Broadband services: IP aggregation, peering edge and multi-access broadband network edge functions including broadband network gateway (BNG), security gateway (SeGW) and hybrid access gateway (HAG)
- Mobile services: IP aggregation, IP security gateway, WiLAN gateway and multi-access edge in IP mobile anyhaul
- Enterprise VPN services: IP aggregation, provider edge (PE), internet access, and cloud and data center interconnect (DCI) services
- Core router: Internet/BGP peering, MPLS switching and backbone infrastructure

- Data center locations: Gateway and interconnect and internet/peering functions

For webscale companies looking to maximize application performance, the 7750 SR delivers massive scalability along with leading features for data center edge functions, including aggregation, gateway, interconnect and internet/peering. In the PoP it supports internet/peering edge and core router functions.

For enterprises, the 7750 SR provides high-performance IP routing, including connectivity to the data center, internet and WAN applications.

IP network security: DDoS mitigation

To identify and neutralize volumetric DDoS attacks automatically, the 7750 SR can be combined with Nokia Deepfield Defender software analytics. The solution is uniquely enabled by the massive filtering scale and performance headroom in FP4 silicon that allows the 7750 SR to act as highly precise attack sensor and mitigation element without compromising the performance of any function and service running on it.

Security policies are continuously monitored and tuned using SR OS telemetry from the 7750 SR. With automated workflows in Deepfield Defender, tens of thousands of silicon filters are updated in seconds to respond to changing security conditions without delay. The filters associated with DDoS mitigation are signature ACLs. These are ACLs beyond typical 5-tuple ACLs that only serve to complete DDoS attacks by impacting all traffic. Signature-based ACLs provide surgical payload level inspection capabilities at line rate to truly filter out DDoS traffic.

Network automation

Model-driven management

To simplify and automate network operations, the 7750 SR enables model-driven network element management through the Nokia SR OS. YANG-based data modeling delivers the foundation for programmability, and model-driven interface

support includes NETCONF, gRPC (gNMI and gNOI) and the model-driven CLI (MD-CLI). The Nokia Network Services Platform (NSP) also supports these interfaces using YANG models to customize automation for operational use cases.

SDN integration and automation

The 7750 SR and the programmability of the Nokia SR OS enable multivendor software-defined networking (SDN). Control integration is enabled through OpenFlow, Path Computation Element Protocol (PCEP) and model-driven network element management.

In combination with the Nokia NSP, the 7750 SR can be deployed to introduce scalable and integrated SDN control across IP, MPLS, Ethernet and optical transport layers. The NSP delivers best-in-class SDN capabilities for multi-layer, cross-domain, multi-technology and coordinated management of IP and optical assets.

The NSP supports unified service automation and network optimization with comprehensive path computation capabilities to enable source-based routing and traffic steering with segment routing support, online traffic engineering and resource optimization and elastic bandwidth services for dynamic cloud applications.

Cross-domain management

The 7750 SR is managed by the Nokia NSP, supporting automated network management, service assurance and resource optimization across IP and optical networks and orchestrated network slicing across transport and core domains.

Hardware overview

The 7750 SR is available in four variants and supports a wide range of hardware assemblies. For value-added services and interface extension options, the 7750 SR ESA and 7210 SAS satellites are hardware options external to the 7750 SR. With reference to Table 2, this overview captures the function and capabilities of 7750 SR adapters, modules and systems. All equipment adapters and modules are hot swappable and field replaceable to maximize system uptime.

Input/Output Module (IOM)

The full slot IOM contains the forwarding complex that performs typical functions such as IP/MPLS routing, packet lookups, traffic classification, processing and forwarding, service enablement, and QoS for the 7750 SR-7, SR-12 and SR-12e. Available in two variants, it equips up to two pluggable media dependent adapter-e (MDA-e) types and supports a number of pay-as-you-grow licensable configurations.

The FP4-based IOM5-e delivers up to 1.5 Tb/s FD (non-redundant) and 1.2 Tb/s FD (redundant) per-slot capacity for the 7750 SR-12e. It delivers up to 800 Gb/s FD (non-redundant) and up to 400 Gb/s FD (redundant) per-slot capacity in the SR-7 and SR-12. The FP3-based IOM4-e delivers up to 200 Gb/s FD per-slot performance and is supported on the SR-7, SR-12 and SR-12e.

Media Dependent Adapter (MDA)

MDAs provide modular interface connectivity along with a variety of interface types and density configurations. Ethernet types support ITU-T Sync-E and IEEE 1588v2 for synchronization requirements.

The MDA-e-XP provides up to 750 Gb/s FD performance in a half-slot adapter and is supported in the IOM5-e in the 7750 SR-1, SR-7, SR-12 and SR-12e. It supports QSFP56-DD, QSFP28-DD, QSFP28, QSFP+, SFP28 and CFP2-DCO connectors with flexible breakout options including 10 x 10GE, 2 x 100GE and 4 x 100GE (on the 6-connector QSFP-DD MDA-e-XP). For the 7750 SR-1 and SR-12e, it supports up to 2.0 Tb/s FD of intelligent aggregation and up to 600 Gb/s FD of intelligent aggregation on the and the SR-7 and SR-12.

The MDA-e provides up to 100 Gb/s FD performance in a half-slot adapter and is supported in the IOM4-e and IOM4-e-HS in the 7750 SR-7, SR-12 and SR-12e and by the IOM-e in the 7750 SR-e series. It supports QSFP28, SFP28, CSFP, SFP+ and CFP2 connectors with flexible breakout options, including 10 x 10GE and 4 x 25GE, MACsec along with ITU-T G.709 and FEC optical transport network (OTN) support.

Integrated Service Adapter (ISA)

Available in two variants, ISAs provide specialized processing and buffering for deeper levels of integrated services and advanced applications for the 7750 SR-7, SR-12 and SR-12e. Service support includes: application assurance, Layer 7 stateful firewall, L2TP network server (LNS), carrier grade-network address translation (CG-NAT), IPsec, IP tunneling, wireless LAN gateway (WLGW) and advanced video services. The ISA2 is a half slot adapter delivering up to 40 Gb/s of processing speed and is supported by the IOM4-e. The Multiservice Integrated Service Module (MS-ISM) is a full height module, leveraging two ISA2s and supports up to 80 Gb/s processing speed.

Switch Fabric Module (SFM)

The SFM is available in two primary types. The SFM6-12e enables 1.5 Tb/s FD (non-redundant) and 1.2 Tb/s FD (redundant) connectivity between all slots of the 7750 SR-12e chassis. The hot-swappable fabric cards are 3+1 redundant with active-active load-sharing design or are 4+0 non-redundant in a back-to-back configuration. Two full-height SFM6-12e modules provide the switching functions for the system as well as housing the pluggable control processor module 5 (CPM5). There are also two half-height mini SFM6-12e modules that provide exclusive switching functions for the system.

The SFM6-7/12 enables 800 Gb/s FD (non-redundant) or 400 Gb/s FD (redundant) line rate connectivity between all slots of the 7750 SR-7 and SR-12 chassis. The hot-swappable fabric cards are 1+1 active-active load-sharing design or 2+0 non-redundant in a back-to-back configuration. The full-height SFM6-7/12 modules control the switching functions for the system and house the pluggable CPM5 for investment protection.

Control Processor Module (CPM5)

The CPM5 is housed in a SFM5 and is supported in the 7750 SR-7, SR-12 and SR-12e. It provides the management, security and control plane processing. Central processing and memory are intentionally separated from the forwarding function on the interface modules to ensure system resiliency.

Redundant CPM variants operate in a hitless, stateful failover mode with full nonstop routing and nonstop services.

Power

Power supply units (PSUs) provide modular, redundant AC power for the 7750 SR-1. Power entry modules (PEMs) provide low-voltage DC power for the SR-7 and 7750 SR-12. Advanced power equalization modules (APEQs) provide power for the 7750 SR-12e. The low-voltage DC APEQs deliver up to 2,800 W each. The high-voltage DC APEQs take 260 V-400 V and provide 3,000 W each. AC APEQs take 200 V-240 V single phase and deliver 3,000 W each.

7750 SR-1 compact system

The 7750 SR-1 is a compact, one-slot system with an integrated 1.5 Tb/s FD IOM5-e and a simplex control plane. It houses up to two MDA-e-XPs and supports QSFP56-DD, QSFP28-DD, QSFP28, QSFP+, SFP28 and CFP2-DCO connectors and flexible breakout options including 10 x 10GE, 2 x 100GE and 4 x 100GE. It supports up to 4.0 Tb/s FD of intelligent aggregation and is available in a number of pay-as-you-grow licensable configurations. The AC variant has two rear-mounted modular power supplies. The DC variant comes with integrated dual feeds at the rear of the system. Both systems have modular rear-mounted fans.

7750 SR Extended Services Appliance (ESA)

The Nokia 7750 SR ESA is mounted external to the 7750 SR system. It is used to extend the level of networking functionality and generalized processing for IP/MPLS routing applications for integrated services on the 7750 SR.

The 7750 SR forwards traffic from a selected port at speeds up to 100 Gb/s to connect to the Nokia 7750 SR ESA, relieving high-performance slots from needing to host service processing, value-added services and network functions. Service support includes AA, Layer 7 stateful firewall, CG-NAT, LNS, IPsec, IP tunneling and WiLAN gateway.

7210 Service Access Switch (SAS) satellites

Nokia 7210 SAS satellites provide flexibility and improve the cost efficiency of the 7750 SR. They offer GE, 10GE and SONET/SDH port extension through an external system to the 7750 SR. They can be collocated in the same 7750 SR rack or located remotely, within distance of pluggable optics. 7210 SAS satellites are logically integrated into the 7750 SR with one single IP address. Configuration is done on the 7750 SR and satellites utilize the 7750 SR-s QoS, buffering, multicast and rich service provisioning.

Technical specifications

Table 1. Hardware specifications for the 7750 SR series

	7750 SR-1	7750 SR-7	7750 SR-12	7750 SR-12e
System capacity FD	1.5 Tb/s	<ul style="list-style-type: none"> • 4 Tb/s (non-redundant) • 2 Tb/s (redundant) 	<ul style="list-style-type: none"> • 8 Tb/s (non-redundant) • 4 Tb/s (redundant) 	<ul style="list-style-type: none"> • 13.5 Tb/s (non-redundant) • 10.8 Tb/s (redundant)
Slot capacity (FD)	1.5 Tb/s	<ul style="list-style-type: none"> • 800 Gb/s (non-redundant) • 400 Gb/s (redundant) 	<ul style="list-style-type: none"> • 800 Gb/s (non-redundant) • 400 Gb/s (redundant) 	<ul style="list-style-type: none"> • 1.5 Tb/s (non-redundant) • 1.2 Tb/s (redundant)
Per-slot intelligent aggregation (FD)	4.0 Tb/s	1.2 Tb/s	1.2 Tb/s	4.0 Tb/s
Number of IOM and MS-ISM slots	1 (integrated IOM)	5	10	9
Number of MDAs and ISA2s	2	10	20	18
Cooling	Front to back	Side to back	Front to back	Front to back
System modules	MDA-e-XP, fan module, PSU	SFM6-7/12, SFM5-12, CPM5, IOM, MDA-e-XP, MDA-e, ISA2, MS-ISM, EFT, PEM	SFM6-7/12, SFM5-12, CPM5, IOM, MDA-e-XP, MDA-e, ISA2, MS-ISM, EFT, PEM	SFM6-12e, Mini-SFM6-12e, SFM5-12e, Mini-SFM5-12e, CPM5, IOM, MDA-e-XP, MDA-e, ISA2, MS-ISM, APEQ, Enhanced fan tray (EFT)
Dimensions	<ul style="list-style-type: none"> • Height: 8.9 cm (3.5 in), 2RU • Width: 48.3 cm (19.0 in) • Depth: 62.5 cm (24.6 in) 	<ul style="list-style-type: none"> • Height: 35.56 cm (14.0 in), 8RU • Width: 44.45 cm (17.5 in) • Depth: 64.77 cm (25.5 in) 	<ul style="list-style-type: none"> • Height: 62.23 cm (24.5 in), 14RU • Width: 44.45 cm (17.5 in) • Depth: 64.51 cm (25.4 in) 	<ul style="list-style-type: none"> • Height: 97.79 cm (38.5 in), 22RU • Width: 44.45 cm (17.5 in) • Depth: 76.2 cm (30.0 in)
Weight	<p>DC system</p> <ul style="list-style-type: none"> • Empty: 15 kg (33.0 lb) <p>AC system</p> <ul style="list-style-type: none"> • Empty: 14.38 kg (31.7 lb) 	<ul style="list-style-type: none"> • Empty: 34 kg (75 lb) • Loaded: 70 kg (155 lb) 	<ul style="list-style-type: none"> • Empty: 56.4 kg (124.3 lb) • Loaded: 155.7 kg (343.3 lb) 	<ul style="list-style-type: none"> • Empty: 86.63 kg (191 lb) • Loaded: 211.83 kg (467 lb)
Power	<p>DC power</p> <ul style="list-style-type: none"> • DC input: -40 V to -72 V, 40 A max • Power feed redundancy <p>AC power</p> <ul style="list-style-type: none"> • AC input: 90 V to 127 V/200 V to 264 V AC, 50 Hz/60 Hz, 12 A/10 A • 1+1 redundancy 	<p>DC power</p> <ul style="list-style-type: none"> • DC-40 V to -72 V, 100 A, 4,000 W max or • DC-46 V to -72 V, 100 A, 4,600 W max • 1+1 redundancy <p>External AC power (option)</p> <ul style="list-style-type: none"> • Input voltage: 200 V AC to 240 V AC • Output voltage: 42 V DC to 56 V DC • Current: 50 A 	<p>DC power</p> <ul style="list-style-type: none"> • DC-40 V to -72 V, 162 A max, 6,480 W or • DC-46 V to -72 V, 175 A max, 8,050 W or • DC-49 V to -55 V, 175 A max, 8,575 W or • DC-50.5 V to -72 V, 175 A max, 8,837.5 W • 1+1 redundancy <p>External AC power (option)</p> <ul style="list-style-type: none"> • Input voltage: 200 V AC to 240 V AC • Output voltage: 42 V DC to 56 V DC • Current: 50 A 	<p>DC power</p> <ul style="list-style-type: none"> • DC-40 V to -72 V, 60 A or 80 A per feed or • DC 260 V to 400 V, 13 A per feed • 4+1 redundancy

Table 2. Nokia 7750 SR MDA-e-XP and MDA-e overview

Ethernet speed Connector	Connectors / ports	Maximum density			
		7750 SR-1	7750 SR-7*	7750 SR-12*	7750 SR-12e
MDA-e-XP					
400G/100G/10GBASE QSFP-DD **	6	8/40/120	—	—	72/360/1080
400G/100G/10GBASE QSFP-DD **	3	4/12/60	20/50/300	40/100/600	36/108/540
100G/10GBASE QSFP28 **	12	24/240	—	—	216/2,160
100G/10GBASE QSFP28	6	12/120	60/600	120/1,200	108/1,080
10G/25GBASE (MACsec) SFP28 + 100G/10GBASE QSFP28	16 + 2	32 + 4/40	160 + 20/200	320 + 40/400	288 + 36/360
100GBASE CFP2-DCO	3	12	30	60	108
MDA-e					
10G/25G/100GBASE (MACsec) QSFP28	2	—	20/80/80	40/160/160	36/144/144
100GBASE QSFP28	2	—	20	40	36
25G/10GBASE (MACsec) SFP28	8	—	80	160	144
100GBASE CFP2	1	—	10	20	18
10GBASE SFP+	10, 6	—	100, 60	200, 120	180, 108
10G/100GBASE (MACsec) SFP+	12	—	100	240	216
100GBASE CSFP/SFP	40	—	400	800	720

* The new ess-system-type BOF option allows a 7750 SR-7-B or SR-12-B chassis to operate as a 7450 ESS-7 or ESS-12 chassis.

** With intelligent aggregation

Feature and protocol support highlights

Feature and protocol support within the 7750 SR series includes, but is not limited to, the following.

IP and MPLS routing features

- IP unicast routing:
 - Intermediate System-to-Intermediate System (IS-IS)
 - Open Shortest Path First (OSPF)
 - Routing Information Protocol (RIP)
 - Multiprotocol Border Gateway Protocol (MBGP)
 - Unicast Reverse Path Forwarding (uRPF)
- Comprehensive control plane protection features for security
- IPv4 and IPv6 feature parity
- IP multicast routing:
 - Internet Group Management Protocol (IGMP)
 - Multicast Listener Discovery (MLD)
 - Protocol Independent Multicast (PIM)
 - Multicast Source Discovery Protocol (MSDP)
 - Bit Indexed Explicit Replication (BIER)
 - IPv4 and IPv6 feature parity

- MPLS:
 - Label Edge Router (LER) and Label Switch Router (LSR) functions with support for seamless MPLS designs
 - MPLS-Transport Profile (MPLS-TP)
 - Label Distribution Protocol (LDP) and Resource Reservation Protocol (RSVP) for MPLS signaling and traffic engineering
 - Includes Point-to-Point (P2P) and Point-to-Multipoint (P2MP) Label Switched Paths (LSPs) with Multicast LDP (MLDP), P2MP RSVP and weighted Equal Cost Multi Path (ECMP)

Segment Routing and SDN features

- Segment Routing Flexible Algorithms for SR-MPLS and SRv6 (128-bit and micro-segment) data plane
 - Nokia SR OS platforms support intra-area and/or inter-area shortest path using IGP metric, TE-metric or delay, as well as traffic engineered tunnels. In addition, SR OS supports selecting a subset of links to be included or excluded for each flexible algorithm.
- Multiple-instance IS-IS and OSPF SR support with shortest path tunnel, Segment Routing - Traffic Engineering (SR-TE) LSP, flexible algorithms, and static and BGP SR policy.
 - Implementation provides Loop Free Alternate (LFA), remote LFA and Topology Independent - LFA (TI-LFA) protection for all types of tunnels as well as end-to-end protection with primary/secondary paths for SR-TE tunnels and SR policies.
 - PCEP allows delegation of the SR-TE LSP to the Nokia NSP or a third-party PCE function
- Programmable forwarding tables via gRPC-based routing information base (RIB) API feature and MPLS forwarding policy
- Extensive set of capabilities using ACL logic to steer routes/flows towards various target types, such as IP next-hop, SR-TE/RSVP-TE/MPLS-TP LSP and Virtual Routing and Forwarding (VRF)
 - Applicable to a wide range of routing and service contexts, such as global routing table,

Virtual Private Routed Network (VPRN), virtual private LAN service (VPLS) and E-Pipe service

- Supports control interfaces such as OpenFlow, FlowSpec, CLI and NETCONF
- Multivendor SDN control integration through OpenFlow, PCEP, BGP-Link State (BGP-LS) and BGP SR Policy support
- Collection of traffic statistics on an extensive set of constructs:
 - LDP
 - RSVP-TE, and SR-TE LSPs
 - MPLS forwarding policies
 - SR-MPLS and SRv6 policies
 - RIB API tunnel entries
 - Interior Gateway Protocol (IGP) SIDs

Layer 2 features

- Ethernet LAN (E-LAN): BGP-VPLS, Provider Backbone Bridging for VPLS (PBB-VPLS), EVPN and PBB-EVPN
- E-Line: BGP Virtual Private Wire Service (BGP-VPWS), EVPN-VPWS and PBB-EVPN
- E-Tree: EVPN and PBB-EVPN
- DCI: EVPN Virtual eXtensible LAN (VXLAN) to VPLS/EVPN-MPLS/EVPN-VXLAN gateway functions

Layer 3 features

- IP-VPN, enhanced internet services
- EVPN for Layer 3 unicast and Optimized Inter-Subnet Multicast (OISM) services with Integrated Routing and Bridging (EVPN-IRB)
- Multicast VPN (MVPN), which includes inter-AS MVPN and Next Generation MVPN (NG-MVPN)
- EVPN and IP-VPN gateway interworking, including D-PATH attribute for loop protection in redundant gateways
- Seamless MPLS/SRv6 integration with IP-VRF for interworking or migration between MPLS and SRv6 transport technologies

System features

- Ethernet satellites: Port expansion through local or remote Nokia 7210 SAS-S series GE, 10GE, 100GE and SONET/SDH satellite variants, offering 24/48 x GE ports, 64 x GE/10GE ports or legacy SONET/SDH ports over GE, 10GE and 100GE uplinks
- Extensive fault and performance monitoring. Operations, Administration and Maintenance (OAM) includes:
 - Ethernet Connectivity Fault Management (CFM) (IEEE 802.1ag, ITU-T Y.1731)
 - Ethernet in the First Mile (EFM) (IEEE 802.3ah)
 - Bidirectional Forwarding Detection (BFD), including Seamless BFD
 - Cflowd
 - Two-Way Active Measurement Protocol (TWAMP and TWAMP Light/STAMP)
 - A full suite of MPLS and Segment Routing OAM tools
- Timing:
 - ITU-T Synchronous Ethernet (SyncE)
 - IEEE 1588v2 Precision Time Protocol (PTP)
 - Network Time Protocol (NTP)
 - BITS ports (T1, E1, 2M)
 - 1PPS
- QoS:
 - Flexible intelligent packet classification
 - Ingress and egress hierarchical QoS (H-QoS) with multitiered shaping and two-tiered, class-fair hierarchical policing
 - Advanced, scalable network and service QoS
 - End-to-end consistent QoS regardless of oversubscription or congestion
- High availability:
 - Nonstop routing¹
 - Nonstop services¹

- In-Service Software Upgrade (ISSU)¹
- Fast reroute for IP, RSVP, LDP and SR
- Pseudowire redundancy
- ITU-T G.8031 and G.8032
- Weighted ECMP
- Weighted, mixed-speed link aggregation

Management features

- Model-driven management of configuration and state through the MD-CLI, NETCONF and gRPC/gNMI using YANG models; streaming telemetry through gRPC/gNMI subscriptions; operations through NETCONF and gRPC/gNOI
- Enhanced automation framework provides personalization and automation with Python 3
- Event triggered and time-based Python 3 applications
- Full SNMP management support, including configuration, monitoring and traps
- Comprehensive network and node management through the Nokia NSP
- Zero touch provisioning (ZTP) automatically downloads the image and configuration from a server via out-of-band management port or in-band interfaces

Standards support²

Environmental specifications

- Operating temperature: 5°C to 40°C (41°F to 104°F)
- Operating relative humidity:
 - 5% to 85% non-condensing (SR-12e, SR-12, SR-7)
 - 5% to 95% non-condensing (SR-1)
- Operating altitude: Up to 3,960 m (13,000 ft) at 30°C (86°F)

¹ Requires redundant CPM modules

² System design intent is according to the listed standards. Refer to the product documentation for detailed compliance status.

Safety

- AS/NZS 60950.1
- AS/NZS 62368.1
- IEC/EN 60825-1
- IEC/EN 60825-2
- IEC/EN/UL/CSA60950-1 Ed2 Am2
- IEC/EN/UL/CSA 62368-1 Ed2

EMC emission

- AS/NZS CISPR 32 Class A
- CISPR 32 Class A
- EN 55032 Class A
- EN 61000-3-2 (SR-1, SR-12e)
- EN 61000-3-3 (SR-1, SR-12e)
- FCC Part 15 Class A
- ICES-003 Class A
- IEC 61000-6-4
- KS C 9832 (2019) formerly KN 32
- VCCI Class A

EMC immunity

- BT GS-7
- EN 55035
- ES 201 468 (7750 SR-1 only)
- ETSI EN 300 386
- IEC 61000-6-2
- KS C 9835 (2019) formerly KN 35

EMC radio (7750 SR-1 only)

- EN 301 489-1
- EN 301 489-17 (Bluetooth)

Environmental

- ETSI EN 300 019-2-1 Storage Tests, Class 1.2
- ETSI EN 300 019-2-2 Transportation Tests, Class 2.3
- ETSI EN 300 019-2-3 Operational Tests, Class 3.2
- ETSI EN 300 019-2-3 Earthquake

- ETSI EN 300 132-2 DC Power Supply Interface
- ETSI EN 300 132-3-1 HVDC Power Supply Interface (SR-1, SR-12e)
- ETSI EN 300 132-3 AC Systems (SR-1, SR-12e)
- ETSI 300 753 Acoustic Noise, Class 3.2 (7750 SR-1 only)

Directives, regional approvals and certifications

- Directive 2011/65/EU Restriction of the use of certain Hazardous Substances in Electrical and Electronic Equipment (Recast) Directive (including Commission Delegated Directive (EU) 2015/863)
- Directive 2012/19/EU Waste Electrical and Electronic Equipment (WEEE)
- Directive 2014/30/EU Electromagnetic Compatibility (EMC)
- Directive 2014/35/EU Low Voltage Directive (LVD)
- Directive 2014/53/EU Radio Equipment Directive (RED) (SR-1)
- CE Mark - Common Europe
- CRoHS - China RoHS (SR-7, SR-12, SR-12e)
- KC Mark - South Korea
- NEBS Level 3
- RCM Mark - Australia
- UKCA Mark - United Kingdom
- VCCI Mark - Japan

Network Equipment Building System (NEBS)

- ATIS-0600010.03
- ATIS-0600015
- ATIS-0600015.03
- ATIS-0600315 (SR-1, SR-7, SR-12, SR-12e)
- ATT-TP-76200
- GR-63-CORE
- GR-295-CORE (SR7, SR-12, SR-12e)
- GR-1089-CORE
- VZ.TPR.9205 TEEER
- VZ.TPR.9305



MEF certifications

For a list of Nokia CE 1.0-, CE 2.0- and CE 3.0-certified products, refer to the [MEF certification registry](#).

Refer to the 7750 SR product and release documentation for system details on dimensions, weights, hardware, safety standards, compliance agency certifications and protocol support.

About Nokia

At Nokia, we create technology that helps the world act together.

As a B2B technology innovation leader, we are pioneering the future where networks meet cloud to realize the full potential of digital in every industry.

Through networks that sense, think and act, we work with our customers and partners to create the digital services and applications of the future.

Nokia operates a policy of ongoing development and has made all reasonable efforts to ensure that the content of this document is adequate and free of material errors and omissions. Nokia assumes no responsibility for any inaccuracies in this document and reserves the right to change, modify, transfer, or otherwise revise this publication without notice.

© 2023 Nokia

Nokia Oyj
Karakaari 7
02610 Espoo
Finland
Tel. +358 (0) 10 44 88 000

Document code: (March) CID164728